

Type Approval Certificate

This is to certify that the undernoted product(s) has/have been tested with satisfactory results in accordance with the relevant requirements of the Lloyd's Register Type Approval System.

Manufacturer	F.A.MOURIKIS
Address	Kalamki, Corinth, Postal code 20 003, Greece
Type	Plywood And Other Wood Boards
Description	Marine plywood constructed from Okoume and/or Sapelli, with or without decorative outer veneers bonded with melamine urea formaldehyde (MUF) adhesive
Trade Name	Mourikis Okoume Marine Plywood & Mourikis Sapelli Marine Plywood
Application	Marine, offshore and industrial use for the construction of pleasure craft, small craft and other constructions
Specified Standard	BS 1088:2018 BS EN 310:1993 BS EN 314-1:2004 BS EN 314-2:2004 BS EN 1246-3:2016
Ratings	Durability of Okoume (to BS1088:2003) Non-durable Panel thickness (mm): 3, 4, 5, 6, 7, 8, 9, 10, 12, 14, 15, 18, 20, 22, 25, 30, 35, 40, & 45 Veneer thickness (mm): 1.1, 1.5, 2.2, & 3.0

71 Fenchurch Street, London, EC3M 4BS, United Kingdom

Mayur Jogia

Lead Specialist - Non-Metallics to Lloyd's Register EMEA
A member of the Lloyd's Register group

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.

Type Approval Certificate

Durability of Sapelli (to BS 1088:2003)	Moderately-durable
Panel thickness (mm):	3, 4, 5, 6, 9, 12, 15, 18, 20, 22 & 25
Veneer thickness (mm):	1 & 1.5

Other Conditions

Irrespective of the durability of the outer veneer, the overall classification of the panel will be that of non-durable in the case of Okoume or mix Okoume and Sapelli, and moderately durable in the case of Sapelli

This certificate is not valid for equipment, the design, ratings or operating parameters of which have been varied from the specimen tested. The manufacturer should notify Lloyd's Register EMEA of any modification or changes to the equipment in order to obtain a valid Certificate.

The Design Appraisal Document No. and its supplementary Type Approval Terms and Conditions form part of this Certificate.